






 (ELX115 	 (ELX115P 	 (ZLX-15 	 (ZLX-15P 
Axial Sensitivity (SPL, 1 W @ 1 m)	95 dB		96 dB	
Case Material	9-ply, 15mm Plywood, Internally Braced, with Textured Paint	9-ply, 15mm Plywood, Internally Braced, with Textured Paint		
Color	Black	Black		
Speaker Type	Full-range, mid-high, two-way	Full-range, mid-high, two-way		
Woofer Size	381 mm (15")	381 mm (15")		
Frequency Response (-3 dB)	75 - 18000 Hz	56 - 18000 Hz		
Frequency Response (-10 dB)	50 - 20000 Hz	44 - 20000 Hz		
Internal Crossover	Yes	Yes		
Recommended High-Pass Frequency	40 Hz		40 Hz	
Max. SPL/1m (calc)	134 dB Half Space	134 dB		
Coverage (Nominal -6 dB) H	90 °	90 °	90 °	90 °
Coverage (Nominal -6 dB) V	50 °	50 °	60 °	60 °
System Power Handling (Continuous/Program/Peak)	400//1600 Watts			
LF Transducer	(1) EVS-15K, 381mm (15") Woofer	(1) EVS-15K, 381mm (15") Woofer	EVS-15L, 380 mm (15 in) Woofer	EVS-15L, 380 mm (15 in) Woofer
HF Transducer	DH-1K, 39mm (1.5") Titanium Diaphragm Compression Driver	DH-1K, 39mm (1.5") Titanium Diaphragm Compression Driver	DH-1K	DH-1K
Crossover Frequency	17000 Hz	1.7 k Hz	1700 Hz	
Nominal Impedance (Passive)	8 Ω			
Minimum Impedance	7.4 Ω		7 Ω	
Connector Type	Parallel Neutrik® NL4	Parallel Neutrik® NL4	Dual NL4	(2) XLR/TRS Combo Jack, (1) 3.5 mm Input, and (1) XLR link Output
Grill	18GA Steel with Black Powdercoat	18GA Steel with Black Powdercoat	18 Gauge Steel with Black Powder Coat	18 Gauge Steel with Black Powder Coat
Height	708 mm (27.87")	708 mm (27.87")	685 mm (26.97")	685 mm (26.97")
Width	432 mm (17.01")	432 mm (17.01")	423 mm (16.65")	423 mm (16.65")
Depth	382 mm (15.04")	382 mm (15.04")	383 mm (15.08")	383 mm (15.08")
Weight Net	21.9 kg (48.28 lbs)	22.5 kg (49.6 lbs)	16.6 kg (36.6 lbs)	17.3 kg (38.14 lbs)
Nominal Impedance		8 Ω	8 Ω	
Power Rating		1000 W		1000 W
Shipping Weight		29.5 kg (65.04 lbs)	22 kg (48.5 lbs)	23 kg (50.71 lbs)
Frequency Range			44 Hz - 20 kHz	42 Hz - 20 kHz
Maximum SPL			126 dB	127 dB
Power Handling (Continuous / Peak)			250 / 1000 W	
Frequency Response			56 Hz - 18 kHz	55 Hz - 18 kHz
Maximum SPL (1% THD)			0 dB	
Enclosure Material			Polypropylene	Polypropylene

