

# Ui24R Passwords

The Ui24R has 3 different passwords

- 1) **Hotspot (WLAN) password**  
to connect your mobile device with the Ui24R
- 2) **Ui24R network administrator password**  
to change the Ui24R network settings (hotspot, Wi-Fi, LAN)
- 3) **Global Master Protection password**  
to manage access rights if used in multi-user mode (e. g. limited access for other band members)

## Hotspot (WLAN) password

The Ui24R hotspot is enabled per default with

SSID: Soundcraft UI24

password: (none – network security is disabled by default)

The default password **AFTER ENABLING** network security (WPA2) is “scuiwlan” – but change this!

*Resetting of password:*

Type in a new password on your Hotspot Configuration page (network administrator password required).

Also, the password is set on the default value “scuiwlan” with a complete reset of the network configuration (press reset button for 10 seconds while powering on the Ui24R).

## Ui24R network administrator password

This password is required if you want to change your network configuration. Factory default is

user: admin

password: admin

Change this password in NETWORK – CONFIG – ADMINISTRATOR PASSWORD. Current password is required to define a new password.

*Resetting of password:*

A reset of the network configuration does NOT reset the network administrator password => you need a full reset: plug in a USB stick with an empty file “**fullreset.txt**” and press reset button for 10 seconds while powering on the Ui24R. This resets your Ui24R to factory defaults (incl. firmware).

## Global Master Protection password

You can switch on a Global Master Protection to limit the rights of other users on the Ui24R. Per default it is disabled. Enable it on ACCESS page and put in a Global Master Password. You need this password to disable the protection also.

*Resetting of password:*

Plug in a USB stick with an empty file “**masterpass.txt**” and press reset button for 10 seconds while powering on the Ui24R. This resets the Global Master Protection incl. password.